FLHLSTRXL | SteadyMag[™] Magnetic Mount System with Large Barcode Scanner Holder



Includes:

2

- **1** Manual
- 5 Stainless Steel Round Flat Washer (M5 x 10mm x 0.5mm)
- 5 Stainless Steel Nylon Nut (M5 0.8 DIN 985 A2)

Installing the holster to the plate

cavities and install the mounting screws.

- 5 DIN Phillips Flat head A2 Stainless Steel Machine Screw (M5-0.8 x 16mm)
- 1 Mounting Bracket (FLIFT03)

Diagram A

- 4 Base Magnets (SPMAG35MM)
- 1 Composite Device Holster with Installation Hardware (SPHLSTRXL)

Note: We recommend using Loctite Threadlocker for locking screws and nuts in place


Prep: Clean the surface and make sure it is free of dirt, dust, and grease before installing the mounting hardware.

With the mounting plate and base magnets assembled,

proceed to assemble and install the device holster to the bracket. Position the nuts inside the device holster nut

Assembling the magnetic kit


Remove all components from the packaging and assemble the mounting plate with the base magnets as seen in the diagram below.





Locate and prep the mounting location for the Device Holster Holder Plate.

Caution: If installing on a vehicle, take precautions to install the system in a location that does not interfere with operation.



WARNING

CHOKING HAZARD - Keep out of reach from children under 8 yrs. as they can choke or suffocate on parts included with this system


WARNING

Arkon[®] is not responsible for any damages caused to your device or yourself due to the installation or use of this mount. Do not install Arkon[®] products near areas that intefere with operation of vehicles. Arkon[®] assumes no responsibility or liability for injury or death as a result of failure to install in a safe location. Arkon[®] is not responsible for any damages caused to vehicles, product, or people due to the installation or use of this product.



USA (800) 841-0884 **INT'L** (626) 254-9005 Monday - Friday 9 am - 5 pm PST

arkon.com Designed in the USA © Arkon Resources, Inc. Need assistance?






Diagram B

With the nuts positioned and held inside the holster cavities, insert the screws and hand tighten. Complete the installation by tightening the screws with a screwdriver.